

SRX10

PREMIUM FLAT HEAD RESIN

PERFORMANCE CHARACTERISTICS

- Low printhead energy-extra advantage for a resin ribbon
- Excellent durability for chemical & industrial applications
- Extensive abrasion, steam and heat resistance (heat resistant up to 300°C)
- Halogen free
- Resistant to a wide range of chemicals and solvents
- Print quality at high speeds up to 204 mm/sec
- Excellent print definition for clean, durable and dense barcodes
- UL/CSA approved

Flat Head Technology Grades*

EWX10	Premium Wax Best choice for general purpose labelling
GPX10	High Performance Wax General purpose labelling with extra durability
PDX25	Premium Wax Resin Great print performance with very good durability
PDX80	High Performance Wax Resin Great print performance with excellent scratch resistance
SRX10	Premium Resin Extra scratch resistance on synthetic labels
SDX80	Premium Textile Resin Excellent print on textiles with wash resistance

*These ribbon grades are for use with flat head technology printers. We also offer ribbons grades for near edge technology printers and thermal transfer coders.

SRX10

PREMIUM FLAT HEAD RESIN

RIBBON SPECIFICATIONS	
DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	5.8 Microns +/- 0.02
INK TYPE	Resin (flat head technology)
COLOUR	Black
INK MELTING POINT	70°C
DENSITY	2.0

RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS	
DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



Total Barcodes Ltd
9 Grammar School Yard
Trinity Square
Hull
East Yorkshire
HU1 1SE

Tel; 01482 534756

Email: sales@totalbarcodes.co.uk